

MAIN CHARACTERISTICS

- High performance ceramic and plastic body POM - Polyacetal (Excellent precision and high wear resistance)
- > Recommended for several applications such as humidification, fine particles reduction, odour control
- > Adaptable on PVC connectors

SPECIFIC CHARACTERISTICS

- > The nozzles have a hollow cone jet or a full cone jet
- > NAF misting nozzles are suitable for pressures from 5 to 30 bars included
- > Easy assembly and cleaning
- > Removable 50 µm filter
- > Sealing materials: nitrile

APPLICATIONS -

Particularly recommended to refresh people and animals. Tender fruits and vegetables cleaning









HOLLOW CONE CHART

	BLAC	K NAF	WHITE NAF		
Pressure (bar)	Flow rate (ml/min)	Angle	Flow rate	Angle	
5	-	50		70°	
7	-	5		75°	
10	-	-	65	80°	
15	-	ı	75	80°	
20	50	80°	85	80°	
25	60	80°	95	80°	
30	70	80°	103 80°		



FULL CONE CHART

	BLUE NAF		GREY NAF		GREEN NAF		ORANGE NAF	
Pressure (bar)	Flow rate	Angle	Flow rate	Angle	Flow rate	Angle	Flow rate	Angle
5	-	-	-	-	-	-	130	80°
7	-	-	63	60°	100	80°	170	90°
10	50	50°	70	80°	130	89°	220	90°
15	60	70°	95	88°	165	89°	295	93°
20	83	75°	118	92°	195	92°	345	93°
25	93	75°	133	96°	220	96°	398	93°
30	100	77°	148	96°	243	96°	435	93°